

# Pneumatic Tacker

## Type 72/16-422

The light but powerful tacker of the 420 series takes staples type 72 in leg lengths from 4 mm to 14 mm. The low air consumption, long service life and ease of maintenance of this tacker make it a real cost saver. The bottom loading magazine allows easy and quick loading. Further features are the ergonomic design and the integrated silencer. This is a versatile tool for industry and the craftsman.



### Popular applications:

Upholstered furniture, chairs, TV and stereo cabinets, loudspeakers, wicker and rattan furniture, perambulators, automobile industry

Length: 221 mm  
Width: 43 mm  
Height: 144 mm

### Technical data

Type description:	72/16-422 Standard	72/16-422 Contact
Article code:	12000069	12000070
Magazine type :	Bottom loader	Bottom loader
Safety:	-	Contact actuation
Fastener type:	Type 72	Type 72
Magazine capacity:	190	190
Fasteners per strip:	1 x 182	1 x 182
Operating pressure:	5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar	6 bar
Air consumption/operation:	0.3 litre / 6 bar	0.3 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB	L WA, 1 s,d= 87 dB
Weight:	0.95 kg	0.95 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.  
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

### Accessories:

Articel code	Description
14400827	Adjustable roller edge guide (assembly in factory)
14400838	Adjustable roller edge guide (assembly in factory)
14400863	Roller edge guide, resilient (assembly in factory)
14400679	Back nose assembly 3 mm. Please note on orders.
14406023	Back nose assembly 6 mm. Please note on orders.
14403330	Remote valve, compl.

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive  
for Machinery (89/392 EWG)

## Pneumatic Tacker Type 72/16-422

Staples type 72



BeA Deutschland  
Befestigungstechnik GmbH  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)



Description	L = Length mm
72/06 NK Hard	6
72/08 NK Hard	8
72/10 NK Hard	10
72/12 NK Hard	12
72/14 NK Hard	14

Other lengths and finishes are also available on request.

### Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut