

Pneumatic Tacker Type 92/25-553 FL

Lightweight at only 1,5 kg this tool drives BeA type 92 staples from 12 to 25mm. Heavy duty aluminum cylinder and piston insure exceptional durability in high volume production environments. Exhaust muffler for quiet operation. Outward flare nose diverges staple legs outward as the staple legs penetrate material being fastened. The outward flare nose can be adjusted for the amount of staple leg flare. Excellent for fastening ticking to foam rubber box spring covers in bedding.



Popular applications:

Ticking fabric to foam rubber box spring borders in bedding, fences,

Length:	203 mm
Width:	47 mm
Height:	178 mm

Technical data

Type description:	92/25-553 FL Flare
Article code:	12000450
Magazine type :	Bottom loader
Safety:	-
Fastener type:	Type 92
Magazine capacity:	111
Fasteners per strip:	1 x 100
Operating pressure:	5 – 6 bar
Max. operating pressure:	6 bar
Air consumption/operation:	0,45 litre / 6 bar
Trigger frequency:	-
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 80 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 88 dB
Weight:	1,45 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description
14405569	Remote Valve
14405571	Mounting flange

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive for Machinery (89/392 EWG)

Pneumatic Tacker Type 92/25-553 FL

Staples type 92



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
92/10 NK HZ	10
92/12 NK HZ	12
92/15 NK HZ	15
92/18 NK HZ	18
92/21 NK HZ	21
92/25 NK HZ	25

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut